



Overview

Epson projectors use 3LCD Engines that have no colour wheel with a white segment and therefore don't force a tradeoff between white and colour brightness. Our newly developed phosphor wheel is made of inorganic material with superior light and heat-resistance to deliver excellent reliability.

Experience complete peace of mind with the 20,000 hours or 5 year warranty (whichever comes first). This ensures reliable long-term performance and gives you the freedom to concentrate on your presentations.

Enjoy the flexibility of running your projector 24/7 with guaranteed performance and reliability. With Epson's latest generation of inorganic LCD panels and unique optimised cooling systems, the L Series projectors are capable of 24/7 use warranted up to 20,000 hrs. With advanced installation flexibility and continuous use.



Features

- Laser Light Source
- 3LCD, 3-Chip Technology
- 4K Enhancement
- WUXGA (1920 x 1200) Resolution
- 8,000 Lumens
- 360° Installation
- 24/7 Operation



Technical specifications

Projection System	RGB liquid crystal shutter projection system
LCD Panel	0.76-inch (D10)

Optical

Zoom	1 - 1.6 (Optical)
Screen Size (Standard Lens)	50" to 300" [1.53m to 9.44m] (Zoom: Wide) 50" to 300" [2.48m to 15.10m] (Zoom: Tele)
Projection Distance (Standard Lens)	100" screen 3.11m - 5m
Throw Ratio	1.45 (Zoom:Wide), 2.32 (Zoom:Tele)
Projection Lens F Number	1.7-2.3
Projection Lens Focal Length	24.02mm - 38.24mm
Focus Method	Powered

Image

Colour Light Output	8,000 Lumens
White Light Output	8,000 Lumens
Resolution	WUXGA
Native Aspect Ratio	16:10
Contrast Ratio	2,500,000:1
Light Source	Laser Diode
LD Input Power	430 W
Keystone Correction (Standard Lens)	Vertical: -45 to +45 degrees Horizontal: -30 to +30 degrees
Lens Shift (Standard Lens)	Vertical: -67% to +67% (Powered) Horizontal: -30% to +30% (Powered)

Connectivity

Input: Video	1 x 5BNC
Input: Computer	1 x D-sub 15-Pin (RGB)
Input: Digital	1 x HDMI, 1 x DVI-D, HDBaseT
Input: Audio	3 x Stereo mini
Input: Control	1 x RS232c, 1 x Stereo mini (Remote)
Input: Network I/O	1 x RJ45, 1 x USB Type A (for optional Wireless LAN unit)
Input: HDBaseT	1 x RJ45
Wireless Connectivity	Optional
Optional Output: Video	1 x Monitor Out (via D-sub 15-pin)
Output: Audio	1 x Stereo mini

Advanced Features

EasyMP Network & Control	Yes
EasyMP Network Projection	-
EasyMP Multi PC Projection	yes
Wireless LAN	Optional
4K Enhancement	yes
Lens Position Memory	Yes (10 positions)
Split Screen	yes
Edge Blending	yes
Curved Screen Projection	yes
Corner Wall Projection	yes
Frame Interpolation	yes
360 Degree Projection	yes
Instant Off	yes
Direct Power On/Off	yes
Security	Kensington® - style lock provision Wireless LAN Unit Lock Security cable hole
Colour Modes	Dynamic, Presentation, Cinema, sRGB, DICOM SIM, Multi-Projection

General

Dimensions D x W x H (Including Feet)	492 x 586 x 211 mm
Weight	Approx. 20.7kg (Including LM08 Lens)
Projector Warranty	5 Years*
Power Consumption: LD On	625W
Power Consumption: Standby	2.4W
Projection Lens Focal Length	24.02mm - 38.24mm
Noise Level	Normal/Quiet: 35/29 dB

*Please note: specs subject to change without notice



WHAT'S IN THE BOX

EB-L1300UNL Projector, 3m Power Cable, 1.8m Computer Cable, Remote Control, 2 x AA Batteries, Cable Cover, Manual, Projection Software CDROM. (Lens not Included)

