



Overview

All HDi interactive boards have true multi touch capabilities. Our boards come with a minimum of 4-touch capability providing the user access to a number of user-friendly gesture recognition tools.

Together with its plug-and-play as well as driverless feature, a user can rest assured that they have a board that will work on Windows, Mac OSX and Linux operating systems.

The user simply plugs the board into the computer and it-justworks. There is no need to install drivers or mess with changing firmware to recognise separate operating systems.

The board itself is made up of sturdy material and with the steel backing its structural integrity is maintained preventing it from warping.

The dry-erase-pen friendly surface means a user is able to use their normal marker pens. Together with the scratch-resistant surface also means the user can use the board in the same way as a normal whiteboard. HDi interactive whiteboards come with pre-mounted brackets ready for easy wall or trolley installation.

Features

- Infra Red (IR) multi touch functionality - Your finger is the mouse, directly touch what you want to control
- True multi-touch – Simultaneous touch anywhere on the board
- Up to 4 points of touch – Includes the commonly used gesture controls (pinch, expand, flick)
- Driverless – Can be used on ANY computer
- Qwizdom OKTOPUST™ licenses (2x User & 5x Collaboration)
- Qwizdom OKTOPUST™ online lesson access (12 months)
- XIMBUS™ for Google Drive™ - presenter to 40 participant subscription (12 months)
- DisplayNote™ - presenter to 5 participant license
- HDi Sketch™ annotation software license (10 users)
- Cross Platform – Can be used on Mac, XP and Windows 7/8
- Marker pen friendly surface – Use as a regular whiteboard and cleans without residue



Size

Total size	105"
Length	2327mm
Width	1312mm
Diagonal	2671mm
Aspect ratio	16:9
Bezel thickness	45mm

Standard Features

Technology	Infrared technology
Writing stylus	Pen, finger, pointer and any other opaque objects
Positioning accuracy	Typical accuracy < 2mm
Response object size	> Ø3.0mm, recommended size: Ø5.0mm
Cursor speed	180 d/s around
Resolution	4096mm (W) × 4096mm (D)
Respond speed	First dot (click): 25ms Continuous dots (write) : 8 ms
Installation instruction	Wall mounting or portable floor stand (optional)
Certification	CE, FCC, RoHs
PC port	USB 1.1, USB 2.0, USB 3.0
Warranty	5 year back to base

Power Supply

Power supply	USB power supply
Voltage	DC 4.6V- 5.0V
Power consumption	<1W (200mA at 5V)

Working Environment

Work temperature	-10°C to 45°C
Storage temperature	-30°C to 60°C
Working humidity	10% to 90%
Storage humidity	0~95%

What's in the box

Nut/bolt	x 8
Bottom bracket	x 2
Stylus	x 4
Warranty card	x 1
CD with calibration software for Win and Mac	x 1
Pen tray	x 1
USB cable (5m)	x 1
Wall mounting strip	x 1

